## Artnet PDD Power Data Distributor



ATIONS	
Connectivity  Ethernet  Cabling Type  Port Sensing  Output Connector	RJ45 (Lock Type Connector)
	10 BASE-T/100 BASE-TX
	Auto Negotiation, MDI/MDIX
	Box Header 50 pin (16 Port Output)
Capacity Capacity Pixels / Universe Pixels / Port	32 Universe
	170 pixels
	256 pixels
Power Input Power Consumption	22 ~ 50 VDC (Recommend : 24VDC)
	Max. 5.0W
Supported Signal Output Signal Output Channels	Art-Net
	SDI (Serial Data Interface)
	16 x SDI
Functions Display Buttons	16 Characters, 2 Lines (Yellow OLED)
	5 Buttons (Arrow key Type)
Environmental Operating Temperature Storage Temperature Material Location	-20°C ~ 50°C / -4°F ~ 122°F
	-30°C ~ 70°C /-22°F ~ 158°F
	Aluminum
	Indoor, Inside PSU Box
Physical Dimension (W x D x H) Weight	166 x 83 x 49 mm (box size only, excluding bracket)
	About 397g
	Ethernet Cabling Type Port Sensing Output Connector Capacity Pixels / Universe Pixels / Port Power Input Power Consumption Input Signal Output Signal Output Channels Display Buttons Operating Temperature Storage Temperature Material Location Dimension (W x D x H)



